


samaritan® PAD 360P

Fully Automatic Public Access Defibrillator

Compact, Easy-to-Use, Lifesaving Technology

Sudden Cardiac Arrest (SCA) is a leading cause of death globally. As response time is critical for survival, the use of an AED can increase the survival rate from 5% to up to 70%, if used within the first few minutes of the SCA.

The samaritan® PAD family of public access defibrillators is designed especially for use in public areas by providing a sophisticated defibrillator for adult or pediatric use, inside a lightweight and easy-to-operate system. Offering all the key features of the samaritan PAD products, the samaritan PAD 360P is a fully automatic defibrillator designed to analyse heart rhythm and automatically deliver a life-saving electrical shock (if needed). The SAM 360P also includes a motion detection feature to warn users of excessive or unexpected patient movement.




Compact in Size, Long on Ability

Portable and lightweight. The samaritan PAD 360P is lighter (1.1 kg/2.4 lbs) and smaller than other defibrillators.

Durable. The samaritan PAD 360P resists shock and vibration and carries an IP56 Rating, the industry's highest rating against dust and moisture ingress. It also carries an eight year unit warranty.

Advanced technology. The samaritan PAD 360P utilizes proprietary electrode technology, advanced and stable firmware, and proprietary SCOPE™* Biphasic technology (an escalating and low-energy waveform that automatically adjusts for patient impedance differences) to assess rhythm and defibrillate if necessary.



Advanced technology balanced against the demands of real world use. At HeartSine, our innovation changes lives. And saves lives.

*Self-Compensating Output Pulse Envelope (SCOPE™) technology automatically compensates energy, slope and pulse envelope for the patient.

Easy-to-Follow Visual and Verbal Guides

User-friendly. The samaritan PAD 360P features easy-to-understand visual and voice prompts that guide a user through the process including CPR coaching.

One-button operation. The samaritan PAD 360P only has one button – ON/OFF, ensuring straightforward operation for all levels of rescuer.

Automatic Shock Delivery. After analysing heart rhythm, the samaritan PAD 360P will automatically deliver a shock (if needed), eliminating the need for the rescuer to push a shock button.

Always ready. A System Status Ready Indicator flashes to show that the complete system is operational and ready for use. The device automatically runs a self-check each week.



Visual cues prompt pad placement



Stand clear of the patient



Safe to touch the patient

Real Economy for the Real World

Two parts, one expiration date. Pad-Pak™ cartridge combines battery and electrode pads, with one expiration date to monitor.

Low cost of ownership. With a shelf life of four years from date of manufacture, the Pad-Pak offers significant savings over other defibrillators that require separate battery and pad units.



Pad-Pak and Pediatric-Pak with pre-attached electrodes.

The HeartSine PAD's built-in intelligence and unique pediatric Pad-Pak ensure the appropriate energy level is delivered for children.



Technical Overview

| Physical | With Pad-Pak™ Inserted |
|----------|------------------------------------------------------|
| Size: | 20 cm x 18.4 cm x 4.8 cm (8.0 in x 7.25 in x 1.9 in) |
| Weight: | 1.1 kg (2.4 lbs) including Pad-Pak Battery |

| Defibrillator | |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Waveform: | Self-Compensating Output Pulse Envelope (SCOPE) Biphasic waveform. Optimized biphasic escalating waveform compensates energy, slope and envelope for patient impedance |

| Patient Analysis System | |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Method: | Evaluates patient's ECG, signal quality, electrode contact integrity and patient impedance to determine if defibrillation is required |
| Sensitivity/Specificity: | Meets ISO 60601-2-4 |

| Environmental | |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Operating/Standby Temperature: | 0°C to 50°C (+32°F to +122°F) |
| Temporary Transportation Temperature: | -10°C to 50°C (14°F to 122°F) for up to two days. Unit must be returned to standby/operating temperature for 24 hours before use. |
| Relative Humidity: | 5% to 95% (non-condensing) |
| Water Resistance: | IEC 60529/EN 60529 IP56 |
| Altitude: | 0 to 15,000 feet (0 – 4,575 meters) |
| Shock: | MIL STD 810F Method 516.5, Procedure I (40 G's) |
| Vibration: | MIL STD 810F Method 514.5+ Category 4 Truck Transportation – US Highways Category 7 Aircraft – Jet 737 & General Aviation (Exposure) |
| EMC: | EN 60601-1-2 |
| Radiated Emissions: | EN55011 |
| Electrostatic Discharge RF Immunity: | EN61000-4-3 80MHZ-2.5GHZ (10 V/m) |
| Magnetic Field Immunity: | EN61000-4-8 (3 A/m) |
| Aircraft: | RTCA/DO-160F, Section 21 (Category M) |
| Falling Height: | 1 meter (3.3 feet) |

| Energy Selection | |
|------------------|---------------------------------------------|
| Adult: | Shock 1: 150J; Shock 2: 150J; Shock 3: 200J |
| Pediatric: | Shock 1: 50J; Shock 2: 50J; Shock 3: 50J |

| Charging Time | |
|---------------------|-----------------------------------------------------|
| New Battery: | Typically 150J in < 8 seconds, 200J in < 12 seconds |
| After 6 Discharges: | Typically 150J in < 8 seconds, 200J in < 12 seconds |

| Event Documentation | |
|------------------------|---------------------------------------------------------------------------------------------|
| Type: | Internal Memory |
| Memory Capacity: | 90 minutes of ECG (full disclosure) and event/incident recording |
| Playback Capabilities: | Custom USB cable directly connected to PC and Saver™ EVO Windows-based data review software |

| Materials Used | |
|----------------|---------------------------------------|
| Housing: | ABS, Santoprene |
| Electrodes: | Hydrogel, Silver, Aluminum, Polyester |

| Pad-Pak — Electrode and Battery Cartridge | |
|------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|
| Adult Pad-Pak* (Pad-Pak-03) and Pediatric Pad-Pak (Pad-Pak-04) <i>* ETSO certified Pad-Pak also available</i> | |
| Shelf Life: | 4 years from manufacture date |
| Weight: | 0.2 kg (0.44 lbs) |
| Size: | 10 cm x 13.3 cm x 2.4 cm (3.93 in x 5.24 in x .94 in) |
| Battery Type: | Lithium Manganese Dioxide (LiMnO ₂) |
| Capacity: | > 60 shocks at 200J 18V, 1.5 Amp Hrs |
| Electrodes: | HeartSine samaritan® disposable defibrillation pads are supplied as standard with each device |
| Placement: | Anterior-lateral (Adult); Anterior-posterior (Pediatric) |
| Active Gel Area: | 100 cm ² (15.5 in ²) |
| Cable Length: | 1 meter (3.3 feet) |

Lifesaving, Pure and Simple

Authorised Distributor

U.S./Americas
HeartSine Technologies, Inc.
121 Friends Lane, Suite 400
Newtown, PA 18940
Toll Free: (866) 478 7463
Tel: +1 215 860 8100
Fax: +1 215 860 8192
info@heartsine.com

Europe/Rest of the World
HeartSine Technologies, Inc.
203 Airport Road West
Belfast, Northern Ireland
BT3 9ED
Tel: +44 28 90 93 94 00
Fax: +44 28 90 93 94 01
info@heartsine.com



The products described in this brochure all meet the applicable European Medical Directive requirements.



UL Classified.
See complete marking on product.



www.heartsine.com